

XP 120



Technical Specification

	Zowell	XP40	XP50	XP60	XP70
Load capacity	kg	4000	5000	6000	7000
Load center	mm	850	850	850	850
Wheelbase	mm	2205	2205	2205	2205
Weight(w/o battery)	kg	1550	1650	1650	1700
Driving wheel size	mm	Φ248×75	Φ248×75	Φ248×75	Φ248×75
Loading wheel size	mm	Φ125×50	Φ125×50	Φ125×50	Φ160×50
Balancing wheel size	mm	Φ90×88	Φ150×50	Φ150×50	Φ150×50
Overall width	mm	900	900	900	900
Overall length	mm	2767	2767	2767	2767
Turning radius	mm	2500	2536	2536	2536
Fork width	mm	700	700	700	700
Drive motor rating	kw	3	3	3	3
Lift motor rating	kw	3	3	3	3

	Zowell	XP80	XP100	XP120
Load capacity	kg	8000	10000	12000
Load center	mm	850	850	850
Wheelbase	mm	435	2258	2258
Weight(w/o battery)	kg	2211	2410	2510
Driving wheel size	mm	Φ248×75	Φ310×140	Φ310×140
Loading wheel size	mm	Φ160×50	Φ200×60	Φ200×60
Balancing wheel size	mm	Φ150×50	Φ150×60	Φ150×60
Overall width	mm	900	1220	1220
Overall length	mm	2767	2840.5	2840.5
Turning radius	mm	2542	2965	2965
Fork width	mm	700	900	900
Drive motor rating	kw	3	4.5	4.5
Lift motor rating	kw	3	6.3	6.3

Client Case



Meet your needs for transporting heavy duty goods